



Hot rolled steel sheets and coils

Environmental Product Declaration (EPD)
In accordance with ISO 14025 and EN 15804 +A1

S-P-01919, version 1.0
UN CPC 412



CONTENT

1. SSAB's vision – a stronger, lighter and more sustainable world	3
2. SSAB in the circular economy	3
3. Product	4
3.1 Technical information and application	4
3.2 Product composition	4
3.3 Compliance with chemical legislation	5
4. Production	6
4.1 Production sites	6
4.2 Labeling and packaging	6
4.3 Sourcing and transportation	6
5. Recycling and waste processing	7
6. Information about safe use	7
6.1 Safety	7
7. LCA information	8
8. Scope of declaration	9
9. Environmental performance	10
10. Additional information	11
11. Mandatory statements	11
12. Program-related information and verification	11
13. References	12
14. Contact information	12

1. SSAB's vision – a stronger, lighter and more sustainable world

SSAB is a specialized global steel company driven by close relationships with our customers. SSAB develops and markets high performance steels that are either high strength or fit for purpose products designed for better performance and sustainability.

The company is a leading producer in the global market for Advanced High Strength Steels (AHSS) and Quenched & Tempered Steels (Q&T). We serve segments such as, automotive, mining and construction with strip, plate and tube products. SSAB's steels and services help to make end products lighter and better engineered, increasing their strength and lifespan.

SSAB has a cost-efficient and flexible production system. SSAB's production plants in Sweden, Finland and the US

have an annual steel production capacity of approximately 8.8 million tonnes. In Sweden and Finland, the integrated blast furnace process is used, whereas in the US, electric arc furnaces are used in a scrap-based production process.

SSAB has been at the forefront of sustainability in many ways. With confidence deriving from our traditions, we now strive to do even more. SSAB aims to be fossil-free as a company by 2045.

SSAB's environmental management is based on the international environmental management systems standard, ISO 14001. All production facilities within the scope of this Environmental Product Declaration have third-party ISO 14001 certification.

2. SSAB in the circular economy

The term circular economy usually is used to describe a transition from linear business models, in which products are manufactured from raw materials, used and then discarded, to circular business models, where products or parts are repaired, re-used, returned and recycled. A circular economy promotes zero waste in order to create a more sustainable world.

In addition, it supports innovative design to promote recycling, a reduction in the amount of virgin materials used, and

encourages the re-use and recycling of all materials. A circular economy can be applied by adopting a lifecycle approach and measuring the social, economic and environmental impact at each stage of a product's lifecycle, including end of life. In summary, steel products promote the core objective of a circular economy because steel can be recycled without weakening its properties.

3. Product

3.1 TECHNICAL INFORMATION AND APPLICATION

SSAB specializes in materials for demanding applications where high strength and formability are needed for weight savings and increased durability. Hot rolled steels are used in many industries and applications, including the construction industry, automotive industry, heavy machinery, shipbuilding and other various metal structures. Hot rolled steel is also used as a raw material for further processing in the manufacture of cold rolled, metal coated and color coated coils and sheets as well as steel tube products.

Hot rolled steels are made in the form of coils that can be slit or cut to length to sheets, in a thickness range of 1.8–25 mm at the Borlänge steel mill in Sweden or the Raabe steel mill in Finland.

SSAB's product portfolio of hot rolled steel sheets and coils consists of a wide selection of steel grades that, for example, range from the most advanced AHSS steels, including complex phase, martensitic and 3rd generation AHSS, as well as hardenable steels, down to conventional C-Mn and HSLA steels.

The products are often customized to meet national and/or international standards as well as customer-specific or other Original Equipment Manufacturer (OEM) standards. Besides standardized steel grades, SSAB's hot rolled product portfolio also includes products unique to SSAB and which in some cases may be patented.

In addition to standard steel grades, the product portfolio includes SSAB's own brands, which are targeted at different segments and applications. The main brands are listed below:

3.1.1 STRENX®

Structural and cold-forming steels for stronger, lighter, safer, more competitive and more sustainable structures.

3.1.2 HARDOX® AND RAEX®

World-leading abrasion-resistant (AR) steels for extended service life and high productivity in challenging environments.

3.1.3 DOCOL®

An Automotive steel to make cars safer and more eco-friendly.

3.1.4 TOOLOX®

A modern engineering and tool steel of unmatched hardness and toughness.

3.1.5 ARMOX® AND RAMOR®

Armor protection steels with quality and performance you can trust.

3.1.6 SSAB BORON

A range of advanced steel grades for quench and press hardening to improve overall productivity, yield and end-product quality.

3.1.7 SSAB DOMEX®

A wide range of structural and cold-forming steels that deliver excellent cold forming, machining and welding performance.

3.1.8 SSAB FORM

Low strength, high formability steels designed to give maximum productivity in stamping, stretching, deep drawing, roll forming, bending, metal spinning and other cold forming procedures.

3.1.9 SSAB LASER®

Structural and cold-forming steels for laser cutting. Designed to improve productivity, yield and end-product quality.

3.1.10 SSAB WEATHERING AND COR-TEN®

Corrosion-resistant steels to minimize total lifecycle costs thanks to low or zero maintenance needs. COR-TEN® is a licensed brand and a part of the SSAB Weathering steel family.

3.1.11 SSAB MULTISTEEL

Covers multiple steel grades and standards bundled into one steel.

Product-specific technical requirements regarding mechanical and other properties arise from national and/or international standards, such as EN 10025 or EN 10149, or customer-specific and/or other OEM standards. SSAB's unique products also have their own specific requirements.

For more detailed information about technical product properties and the product portfolio, please visit www.ssab.com.

3.2 PRODUCT COMPOSITION

Steel is an alloy of mainly iron and carbon, with small amounts of other alloying elements. These elements improve the chemical and physical properties of steel, such as strength, ductility, durability and corrosion resistance. The alloying elements of steel are physically bonded to the steels inherent crystalline structure.

The exact compositions of hot rolled products manufactured by SSAB depend on the requirements of the product. These requirements arise from national and/or international standards, such as EN 10025 or EN 10149, or customer specific and/or other OEM standards. SSAB's unique products also have their own specific requirements.

TABLE 1. EXAMPLE COMPOSITION OF A HOT ROLLED COLD-FORMING STEEL (S355MC)

Material	Content (%) of total product weight	Ingredient	Content (% W/W)	CAS number
Cold-forming steel (S355MC)	100	Iron (Fe)	> 97	7439-89-6
		Carbon (C)	< 0.12	7440-44-0
		Silicon (Si)	< 0.50	7440-21-3
		Manganese (Mn)	< 1.50	7439-96-5
		Vanadium (V)	< 0.20	7440-62-2
		Titanium (Ti)	< 0.15	7440-32-6

Remarks

Physical state: solid
 Odor: odorless
 Color: metallic gray
 Boiling point: 2,750°C
 Melting point: 1,450–1,520°C
 Steel density: 7,850 kg/m³

Table 1 shows as an example the composition of a hot rolled cold-forming steel (S355MC, excluding packaging materials) produced by SSAB for different areas of use. This product is a typical example of a hot rolled steel grade used especially in the construction industry. This information is given based on hot rolled steel products made at SSAB’s sites in both Sweden and Finland.

The values provided are based on European Standards EN 10219-1, EN 10149-2, EN 10025-2, EN 10025-3, EN 10025-4, EN 10025-6, EN 10130, EN 10268, EN10346 and EN 10169 requirements on maximum concentrations, and included in Table 1 if the maximum levels according to these standards are 0.1% by weight, or higher.

More detailed information about the composition of different steels is available from national and international standards as well as from SSAB’s website www.ssab.com.

3.3 COMPLIANCE WITH CHEMICAL LEGISLATION

SSAB actively tracks and anticipates future changes in environmental, safety and chemical legislation and complies with valid EU chemical regulations, such as the REACH Regulation 1907/2006. Communication and cooperation throughout the supply chain plays an important role and SSAB requires full REACH compliance from its subcontractors. SSAB tracks the

list of Substances of Very High Concern (SVHC) and other legislative requirements to ensure products meet legal and customer requirements. In addition, SSAB observes and complies with the requests and recommendations of many customers to withdraw products containing hazardous substances in the customer sector.

SSAB’s steel products do not contain substances of very high concern (SVHC) as defined and listed in the European Chemicals Agency (ECHA) Candidate List of substances of very high concern for Authorisation, in levels above 0.01% by weight.

Steel contains very small amounts of impurities originating from natural raw materials and not added during the steel production process. The amount of impurities in the steels is minimal and, based on knowledge of the toxicity of these substances and their metallurgical bond in the steel matrix, does not pose a risk to the environment or human health.

For the construction industry, the Environmental Product Declaration will give benefits in rating schemes, such as BREEAM, LEED and Miljöbyggnad. Additionally there are specific tools for material evaluation, such as BASTA, Byggarubedömningen and SundaHus, where information from this Environmental Product Declaration is needed.

More information about the chemical composition of hot rolled steel sheets and coils can be found at www.ssab.com.

4. Production

4.1 PRODUCTION SITES

Hot rolled steel sheets and coils are manufactured at SSAB's production sites in Borlänge, Sweden and Raahе, Finland. Steel production is based on the use of iron ore as a raw material. However, SSAB uses approximately 20% of scrap steel in conjunction with steel production in the Nordics. The use of raw materials and energy has been optimized in steel production.

When scrap steel is used instead of virgin raw materials in steelmaking, the carbon dioxide emissions originating in steel production decrease accordingly. Steelmaking at SSAB uses scrap material from SSAB's own production processes and material sourced on the scrap steel market. Once steel has been made, it can be recycled without weakening its properties.

At SSAB, steelmaking processes have been continuously advanced and improved. As a result, SSAB's blast furnaces today are among the most efficient in the world in terms of minimizing carbon dioxide emissions from steel production.

Most of the energy used in ore-based steel production comes from coal, which is used as a reducing agent in iron-making. The mineral products formed in SSAB's iron and steel production processes and the by-products generated in the coking process are recycled as industrial raw material or material to replace virgin resources. A high percentage of the dust originating in various processes is returned to the process to reduce waste and improve material efficiency.

4.2 LABELING AND PACKAGING

Products are labeled to be easily and permanently identifiable and traceable. Labeling complies with standards EN 10021 and EN 10204. The packaging and protection of our steel products is usually determined when ordering. Steel or plastic straps, wood props, corner protection and other accessories supporting packaging are used as appropriate and according to customer requirements.

Plastic film is usually used as the packaging material for cut lengths. The bundles are fastened with steel or plastic straps.

Coils are delivered fastened and, depending on the order, plastic film and/or wrapping paper, cardboard wall protection, plastic or metallic end rings and binding straps are used for the packaging. We use steel, plastic and cardboard as corner protection for cut lengths and coils.

This section of the declaration is for information purposes only. The packaging materials are not included in the LCA study.

More information about the labeling and packaging can be found at www.ssab.com.

4.3 SOURCING AND TRANSPORTATION

The general terms and conditions of all new or renewed raw material sourcing contracts require compliance with SSAB's Supplier Sustainability Policy. Ethical values, environmental concerns and energy efficiency are considered when choosing suppliers. As regards the main raw materials used in steel production, iron ore pellets are sourced from Sweden and Russia, metallurgical coal from North America, Australia and Russia, metallurgical coke from Japan, China and Poland, limestone from Sweden, Norway, France and Spain, and scrap from Sweden, Finland and Russia. Alloys are sourced from multiple origins including Brazil, Russia, China, South Korea, Chile and the US. The company's own logistics unit is responsible for most of SSAB's transportation of raw materials and products. Finished products are transported by sea, road or rail.

SSAB's environmental objectives in respect of logistics are managed through a certified environmental management system. The aim is to increase the share of logistics contracts with partners who have signed up for energy efficiency agreements in the logistics and transport sector. Around 85% of SSAB's land transportations per tonne of products are carried by a partner signatory to energy efficiency agreements. Logistics companies outside an energy efficiency agreement are regularly encouraged to sign up to one. SSAB's international partners have certified environmental management systems. Logistics aims to optimize transport and maximize payloads and to combine transport as efficiently as possible.

5. Recycling and waste processing

Steel is a fully recyclable material and scrap steel has a strong market position: steel recovered from structures and end products at the end of their lifecycle is efficiently recycled and re-used.

No hazardous waste is formed from end products and steel does not harm the environment. According to the European

Waste Catalogue, the waste code for steel products manufactured by SSAB after their useful life is 17 04 05 (iron and steel). All packaging materials for steel products can be recycled.

6. Information about safe use

Steel poses no hazards to the environment in the forms supplied. Some grades of steel contain alloying elements such as manganese, chromium, niobium, vanadium, titanium, nickel, copper and silicon. None of these substances is released under normal or reasonably foreseeable conditions of use.

Dust and vapors may form when steel is melted, welded, cut or ground (or heated to very high temperatures). Long-term exposure to high dust and vapor concentrations may affect the health, especially the lungs. The composition of dust and vapor depends on the steel grade and methods employed.

Welding must be left to trained people. Personal protective equipment must be used and sufficient ventilation must be ensured in compliance with safety legislation. Instructions on the welding of metals and metal alloys can be found on the website of, for example, the European Steel Association www.eurofer.org.

The use and handling of steel does not endanger people or the environment and there are no specific exposure limits in place for this reason. Neither have any first aid measures, measures in the event of fire or unintentional emission, or measures as regards the handling and storage of steel been specified.

Normal precautions should be taken to avoid physical injuries caused mainly by the heavy weight or sharp edges of a product. Personal protective equipment such as special gloves and eye protection must be worn.

Hot rolled steel is not classified as dangerous under the EU's chemical regulation (REACH) and so no Safety Data Sheet or hazardous packaging, marking or transport rules and regulations are required.

6.1 SAFETY

- Always wear gloves and protective clothing when handling steel products.
- Be careful of sharp edges and corners.
- Always use official lifting equipment when moving steel products.
- Never use binding straps to lift a product.
- Straps under tension may cause injury when cut and the outer ring of a coil may rebound outwards.
- Never go under steel products when they are being moved.
- Make sure the securing straps are sufficiently strong and firmly attached.
- Always follow the industrial safety provisions in force and find out whether the installation site is subject to any particular safety requirements before beginning installation work.

7. LCA information

- **Functional unit / declared unit:** 1 tonne (1000 kg) of hot rolled steel sheets and coils.
- **Reference service life:** Not applicable.
- **The LCA is based on data from the following SSAB production sites:**
 - SSAB EMEA AB, Luleå, Sweden
 - SSAB EMEA AB, Borlänge, Sweden
 - SSAB Europe Oy, Raahе, Finland
- **Data quality and representativeness:** Production data have been collected by SSAB directly from the production sites and are average values for the year 2017. The data have been measured and verified internally. The data are assumed to be the most relevant according to current conditions and production practices.
- **Database(s) and LCA software used:** The World Steel Association's 5th steel LCI dataset released in December 2018, the GaBi LCA Databases 2019 (SP39), the Gabi LCA Software (GaBi version 9).
- **Description of system boundaries:** Cradle-to-gate with options.
- **Cut-off:** The packaging material inflow is not included in the LCA. The packaging material represents less than 1% of the total inflow by mass and is therefore well below the limits given by the cut-off rules, stated in EN 15804, as well as the relevant PCR document for this EPD.
- **Allocation:** By-products such as blast furnace slag are used as input material in a number of industries, for example in road construction and as a substitute for cement. This study has used a conservative approach and considered all the environmental burdens associated with the production of the steel products and by-products as belonging to the production of the steel.
- **End-of-Life Scenario:** A recycling rate of 95% has been assumed for the steel product. That is to be seen as the proportion of the material in the product that will be recycled (or re-used) in a subsequent system. The recycling rate referring to the output of the recycling plant and all the material losses through the lifecycle have been taken into account, including material losses in the collection, sorting and recycling (or re-use) processes up to the point of final substitution. The scenario results in 5% material losses in total, considered as landfilling steel scrap.
- **Net-scrap calculation:** To some extent SSAB uses external scrap in the steel production. Therefore, this amount of scrap has been deducted from the stated recycling rate. This is done to calculate the amount of net-scrap to be credited in Module D. This is the amount of steel scrap available for the next lifecycle. The re-circulation of internal scrap has not been considered in this calculation, since it represents a closed loop inside the system boundary for the LCA.

8. Scope of declaration

The scope of this declaration is for 1 tonne of hot rolled steel sheets and coils from cradle to the mill gate, including end-of-life processing and recycling: Modules A1 – A3, C3 – C4 and D (according to EN 15804). Modules A4 – A5, B1 – B7 and C1 – C2 have not been included, due to the inability to predict how the material will be used following manufacture.

The system boundary applied in this study extends from Module A1, the mining of raw materials, such as iron ore and coal; Module A2, transport to and within the manufacturing site; Module A3, coke, iron and steel manufacture; ancillary

service operations; hot rolling of steel products and packaging for dispatch to customers at the exit gate of the manufacturing site.

The system boundary also includes manufacture of other required input materials, transport between processing operations, the production of external services such as electricity, natural gas and water, and the production of by-products within the steelmaking process. Wastes and emissions to air, land and water are also included, as are Modules C3 scrap processing, C4 disposal to landfill and D recovery for recycling.

Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Re-use-, recovery-, recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	X	X	X

X=Module declared.

MND=Module not declared (such a declaration shall not be regarded as an indicator of a zero result).

9. Environmental performance

For SSAB, the Nordic production system should be considered as one entity. A customer order is normally not dedicated to a specific production location, since the technical specification (data sheet) is used to identify the product.

Although there is a spread larger than 10 % for some indicators, it would not be meaningful to report these at site level, since the actual customer business is not conducted at site level.

In the case of hot rolled strip, mainly the indicators ADP and ODP differ, which can be explained by differences in the product mix, rather than the performance of the sites per se. In particular this refers to the alloying content of the products, and the upstream impact thereof.

Tables 2a – 2c show the results of the lifecycle assessment.

TABLE 2A. POTENTIAL ENVIRONMENTAL IMPACT PER 1,000 KG OF HOT ROLLED STEEL SHEETS AND COILS

Parameter	Unit	A1-A3	C3	C4	D
Global warming potential (GWP)	kg CO ₂ equiv.	2.16E+03	2.49E+00	7.44E-01	-1.48E+03
Eutrophication potential (EP)	kg (PO ₄) ³⁻ equiv.	4.16E-01	4.22E-03	5.00E-04	-2.17E-01
Acidification potential (AP)	kg SO ₂ equiv.	3.90E+00	1.76E-02	4.42E-03	-2.93E+00
Photo-oxidant formation potential (POCP)	kg ethene equiv.	4.38E-01	1.95E-03	3.42E-04	-6.86E-01
Ozone Layer Depletion Potential (ODP)	kg CFC11 equiv.	9.67E-11	8.13E-15	4.32E-15	8.29E-06
Abiotic depletion potential: fossil (ADP-fossil)	MJ, net calorific value	2.36E+04	4.83E+01	1.04E+01	-1.44E+04
Abiotic depletion potential: elements(ADP-elements)	kg Sb equiv.	1.27E-03	2.80E-06	7.41E-08	-4.56E-03

TABLE 2B. USE OF RESOURCES PER 1,000 KG OF HOT ROLLED STEEL SHEETS AND COILS

Parameter	Unit	A1-A3	C3	C4	D	
Renewable primary energy	Used as energy carrier	MJ, net calorific value	8.35E+02	3.56E+00	1.37E+00	9.56E+02
	Used as raw materials	MJ, net calorific value	0	0	0	0
	Total	MJ, net calorific value	8.35E+02	3.56E+00	1.37E+00	9.56E+02
Non-renewable primary energy	Used as energy carrier	MJ, net calorific value	2.41E+04	5.01E+01	1.08E+01	-1.39E+04
	Used as raw materials	MJ, net calorific value	0	0	0	0
	Total	MJ, net calorific value	2.41E+04	5.01E+01	1.08E+01	-1.39E+04
Secondary material	kg	26	-	-	-	
Renewable secondary fuels	MJ, net calorific value	7.86E-20	0	0	0	
Non-renewable secondary fuels	MJ, net calorific value	9.23E-19	0	0	0	
Net use of fresh water	m ³	1.17E+01	1.49E-02	2.72E-03	1.99E+00	

TABLE 2C. WASTE PRODUCTION PER 1,000 KG OF HOT ROLLED STEEL SHEETS AND COILS

Parameter	Unit	A1-A3	C3	C4	D
Waste, hazardous	kg	2.74E+00	1.57E-06	1.84E-07	-9.72E-04
Waste, non-hazardous	kg	5.19E+01	1.02E-02	5.01E+01	1.60E+02
Waste, radioactive	kg	1.94E-01	0	0	0

10. Additional information

Steel is 100 % recyclable and its unique properties mean it can be recycled without loss of properties or performance.

11. Mandatory statements

- The EPD for construction products may not be comparable if they do not comply with EN 15804.
 - EPDs within the same product category but from different programs or utilizing different PCRs may not be comparable.
-

12. Program-related information and verification

Program	The International EPD® System. EPD International AB, Box 210 60, SE-100 31 Stockholm, Sweden. www.environdec.com
EPD registration number	S-P-01919
Published	2020-03-31
Valid until	2025-03-30
Product group classification	UN CPC 412
Reference year for data	2017
Geographical scope	Global
Core product category rules (c-PCR)	CEN standard EN 15804+A1 served as the core PCR.
Product category rules (PCR)	PCR 2012:01 Construction products and Construction services. Version 2.3, 2018-11-15.
PCR review was conducted by	The Technical Committee of the International EPD® System. Chair: Massimo Marino. Contact via info@environdec.com
Independent verification of the declaration and data, according to ISO 14025:2006:	<input type="checkbox"/> EPD Process Certification (internal) <input checked="" type="checkbox"/> EPD Verification (external)
Third party verifier	Carl-Otto Nevén NEVÉN Miljökonsult
Accredited or approved by	The International EPD® System.

13. References

- ISO 14025:2006 Environmental labels and declarations — Type III environmental declarations — Principles and procedures.
- General Programme Instructions of the International EPD® System. Version 3.01.
- EN 15804:2012 +A1:2013 Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products.
- PCR 2012:01. Construction Products and Construction Services. Version 2.3, 2018-11-15.
- World Steel Association Life Cycle Inventory study report, 2018 data release. This study report corresponds to the steel LCI data released in December 2018 for 17 products. This is the 5th worldsteel LCI study and has been carried out in accordance with the worldsteel LCI methodology report.
- The GaBi LCA Databases 2019 (SP39).
- The GaBi LCA Software (GaBi version 9).
- LCA methodology report – SSAB steel products EPDs, as the basis for the publication of EPDs within The International EPD® System, IVL Report U 6256, 2020.

14. Contact information

EPD owner	SSAB EMEA AB SE-781 84 Borlänge Sweden www.ssab.com Jonas Larsson
LCA author:	IVL Swedish Environmental Research Institute Valhallavägen 81 114 27 Stockholm Sweden www.ivl.se Elisabeth Hallberg
Program operator	EPD International AB info@environdec.com

SSAB is a Nordic and US-based steel company. SSAB offers value added products and services developed in close cooperation with its customers to create a stronger, lighter and more sustainable world. SSAB has employees in over 50 countries. SSAB has production facilities in Sweden, Finland and the US. SSAB is listed on the Nasdaq OMX Nordic Exchange in Stockholm and has a secondary listing on the Nasdaq OMX in Helsinki.